Epoxy



60Z EPOXY KIT



EPOXY TUBE & GUN



2 GAL EPOXY KIT



EPOXY MIXER NOZZLE FOR USE WITH TWIN TUBE EPOXY

ADH-EPOXY 6OZ ADH-EPOXY TUBE ADH-EPOXY GUN ADH-EPOXY MIXER ADH-EPOXY 2GAL 6 OZ A/B EPOXY KIT
600ML (20 OZ) A/B EPOXY TUBE
EPOXY GUN
MIXER NOZZLE FOR EPOXY TUBE
2 GALLON A/B EPOXY KIT



T 760-884-3735 F 760-737-0450 TrafficSupplyInc.com

Epoxy adhesives have long been used to secure pavement markers and surface mount delineators.

Proper surface preparation is essential:

- Surface should be dry and swept or blown free of debris.
- New asphalt and concrete surfaces must have had sufficient time to set.
- Alternate products should be used if the surface has frequent standing water, is frequently irrigated or has an abnormally high moisture content.

Tech notes:

- This is a standard set product. Have the layout work done prior to mixing the epoxy and plan to keep traffic off of the device until the epoxy has had time to set.
- Uncured epoxy will generate heat and become uncomfortably warm as it sets.
- Follow the PPE, storage and clean up recommendations on the SDS.
- One 6oz epoxy kit will set 2 RPM's or 1 surface mount delineator.
- One 600ml (20oz) epoxy tube will set 6 RPM's or 3 surface mount delineators.
- One 2 gallon epoxy kit will set 85 RPM's or 42 surface mount delineators.