



END ROAD WORK
G20-2

ROAD WORK AHEAD
W20-1

NARROW LANE
C12 (CA)

NARROW LANE
C12 (CA)

KEEP RIGHT
R4-7a

12' MIN. (1)

12' MIN. (1)

100' Taper (optional)

TEMPORARY "NO PARKING" AREA

TEMPORARY "NO PARKING" AREA

DETOUR AHEAD
W20-2

NARROW LANE
C12 (CA)

NARROW LANE
C12 (CA)

ROAD WORK AHEAD
W20-1

- SEE GENERAL NOTES
1. 14' MINIMUM ON ROADWAY WITH BIKE LANES
 2. CONES OPTIONAL WHERE NO PARKING IS ALLOWED

LEGEND

- CONE
- ⊕ BARRICADE
- ▬ FLASHER
- ▬ SIGN
- ▨ WORK AREA
- ⇄ TRAFFIC DIRECTION

AGENCY ENGINEER'S COMMENTS

POSTED SPEED LIMIT	APPROACH SPEED	TAPER LENGTH	SPACING OF CONES	SIGN SPACING	BUFFER LENGTH

GENERAL NOTES

See TC-4 for sign spacing, spacing of cones, and taper and buffer lengths. For hours of darkness, change cones to vertical barricades with steady burn lights. This plan DOES NOT apply to signalized or multi-way stop intersections. Consult the local jurisdiction when preparing Traffic Control Plans near these intersections. This plan MAY NOT apply when the work area affects bike lanes, sidewalks, pedestrian access and curved or narrow roadways. Consult the approving agency when preparing the Traffic Control Plan or these areas. Nothing contained on this drawing shall prevent local jurisdictions from modifying, changing or adopting new specifications deemed necessary. Criteria for position, location and use of Traffic Control Devices is solely for the purpose of guidance to assist in the set up of the Traffic Control Plans. TC-5 is required for all Traffic Control Plans.

AGENCY USE

APPLICANT USE

SUBMITTED BY:
NAME _____
COMPANY _____
ADDRESS _____
PHONE _____

Revision	By	Approved	Date
DRAWING	CRH		4/06
ORIGINAL		<i>[Signature]</i>	4/27/06

APPENDIX "A"
SAN DIEGO REGIONAL STANDARD
SIDE OF ROAD WORK AREA
TWO LANE TRAFFIC CONTROL
WITH CENTERLINE

DRAWING NUMBER **TC-7**