



SIGN SPACING
SEE TC-4
USE FOR ALL
INTERSECTION LEGS

END ROAD WORK
G20-2

NARROW LANE

SHIFT TAPER (1/2L)
12' MIN. (1)

TEMPORARY
NO PARKING
AREA

ROAD WORK AHEAD W20-1
NARROW LANE C12(CA)
NARROW LANE C12(CA)
END ROAD WORK G20-2

1. 14' MINIMUM ON ROADWAY WITH BIKE LANES
2. LEFT OR RIGHT TURN MOVES MAY BE RESTRICTED
3. SEE T.C. 41 FOR PEDESTRIAN CONTROLS

LEGEND

- CONE
- ⊕ BARRICADE
- ▬ FLAGGER
- ▬ SIGN
- ⚡ FLASHING ARROW SIGN
- ▨ WORK AREA
- ↔ TRAFFIC DIRECTION

AGENCY ENGINEER'S COMMENTS

POSTED SPEED LIMIT	APPROACH SPEED	TAPER LENGTH	SPACING OF CONES	SIGN SPACING

SEE TC-4 FOR
SIGN, CONE
SPACING AND
TAPER LENGTH

GENERAL NOTES

For hours of darkness, change cones to vertical barricades with steady burn lights.
This plan MAY NOT apply to signalized or multi-way stop intersections. Consult the local jurisdiction when preparing Traffic Control Plans near these intersections.
This plan MAY NOT apply when the work areas affect bike lanes, sidewalks, pedestrian access and curved or narrow roadways. Consult the approving agency when preparing the Traffic Control Plan or these areas.
Nothing contained on this drawing shall prevent local jurisdictions, from modifying, changing or adopting new specifications deemed necessary. Criteria for position, location and use of Traffic Control Devices is solely for the purpose of guidance to assist in the set up of the Traffic Control Plans.
TC-5 is required for all Traffic Control Plans.

AGENCY USE

APPLICANT USE

SUBMITTED BY:
NAME _____
COMPANY _____
ADDRESS _____
PHONE _____

Revision	By	Approved	Date
DRAWING	CRH		4/06
ORIGINAL		<i>[Signature]</i>	4/27/06

APPENDIX "A"
SAN DIEGO REGIONAL STANDARD
CENTER OF ROAD WORK AREA
INTERSECTION TRAFFIC CONTROL

DRAWING NUMBER TC-29