



APPENDIX "A"
SAN DIEGO REGIONAL STANDARD
SIDE OF ROAD WORK AREA
 MULTILANE ROADWAY WITH RAISED MEDIAN

TRAFFIC DIRECTION

LEGEND

● CONE + BARRICADE FLAGGER SIGN FLASHING ARROW SIGN WORK AREA

SEE TC-4 FOR SIGN, CONE SPACING AND TAPER LENGTH

POSTED SPEED LIMIT	APPROACH SPEED	TAPER LENGTH	SPACING OF CONES	SIGN SPACING

GENERAL NOTES

For hours of darkness, change cones to vertical barricades with steady burn lights. This plan DOES NOT apply to signalized or multi-way stop intersections. Consult the local jurisdiction when preparing Traffic Control Plans near these intersections. This plan MAY NOT apply when the work areas affect bike lanes, sidewalks, pedestrian access and curved or narrow roadways. Consult the approving agency when preparing the Traffic Control Plan or these areas.

nothing contained on this drawing shall prevent local jurisdictions from modifying, changing or adopting new specifications deemed necessary. Criteria for position, location and use of Traffic Control Devices is solely for the purpose of guidance to assist in the set up of the Traffic Control Plans. TC-5 is required for all Traffic Control Plans.

AGENCY ENGINEER'S COMMENTS

AGENCY USE

APPLICANT USE

SUBMITTED BY:

NAME _____

COMPANY _____

ADDRESS _____

PHONE _____

DRAWING NUMBER	TC-42	APPENDIX "A" SAN DIEGO REGIONAL STANDARD SIDE OF ROAD WORK AREA MULTILANE ROADWAY WITH RAISED MEDIAN	Revision	By	Approved	Date
			DRAWING	CRH		4/06
			ORIGINAL		<i>[Signature]</i>	4/27/06